



“Electronic Components Synthesis”, Ltd.

“SYNTEC”

Russia, 302020, Orel, Naugorskoe shosse, 5.

Tel./Fax: (4862) 45-53-20, E-mail: [syntec@orel.ru](mailto:syntec@orel.ru), [www.syntec.orel.ru](http://www.syntec.orel.ru)

**Optoelectronic module 9C0.7A400II4 400V / 0,7A**

ИКАИИ.431156.003TY ГК

<p><u>Peculiarities:</u></p> <ul style="list-style-type: none"> <li>- Control current 10 mA</li> <li>- 5 000 V Dielectric strength</li> <li>- 4-pin plastic SIP, Pin step 2,5 mm</li> </ul>	<p style="text-align: center;">Circuit diagram</p>	<p style="text-align: center;">Outline drawing</p>
<p>Switching-on circuits</p>		
<p style="text-align: center;">Circuit A</p>	<p style="text-align: center;">Circuit B</p>	

**ELECTRICAL PARAMETERS**  $T_{amb} = 25^{\circ}C$

Parameter name	Sign	Unit	Value			Measurement mode
			Min.	Typ.	Max.	
Input Voltage	$U_i$	V	2,1		3,0	$I_i=10mA$
Output Resistance in ON condition	$R_{ON}$	Ohm			3,6	$I_i=10mA; I_o=0,7A; t=1sec.$
Output Leakage Current in OFF condition	$I_{leak}$	$\mu A$		0,2	100	$U_i=0,8V; U_o= 400V$
Dielectric Strength: Input-Output	$U_{diel.s}$	V	5000			$t=1min.$
Insulation Resistance	$R_{ins}$	Ohm		$10^{11}$		$U_{diel.s}=500V$
Turn-on time	$t_{on}$	ms		7	10	$U_o=60V; R_l=1kOhm; C_l=25pF;$
Turn-off time	$t_{off}$	ms		1	2	$I_i=10mA$

**PERMISSIBLE OPERATING CONDITIONS**

Condition parameters	Units	Min.	Max.	Note	
Input on-state Current	mA		25		
Peak Input Current	mA		150	$t_i < 100\mu s$	
Input off-state Voltage	V	-3,5	0,8		
Operating Voltage	V	-400	400		
Irms	Circuit A	A	-0,7	0,7	$T_{amb}=25^{\circ}C; I_i=10mA$
	Circuit B			1,4	
Temperature coefficient of max. Irms	Circuit A	mA/ $^{\circ}C$	-4,8		$25^{\circ}C < T_{amb} \leq 85^{\circ}C;$ $I_i=10mA$
	Circuit B		-9,6		
Pulse Load Current	Circuit A	A	-4,2	4,2	$T_{amb}=25^{\circ}C; I_i=10mA;$ $t=200 ms; Duty Cycle=50\%$
	Circuit B			8,4	
Temperature coefficient of max. Pulse Load Current	Circuit A	mA/ $^{\circ}C$	-26		$25^{\circ}C < T_{amb} \leq 85^{\circ}C;$ $I_i=10mA$
	Circuit B		-52		
Operating Temperature Range	$^{\circ}C$	-45	85		